

(b) All warranty requirements and subsequent revisions shall be submitted to the Division Administrator for advance approval.

(c) No warranty requirement shall be approved which, in the judgment of the Division Administrator, may place an undue obligation on the contractor for items over which the contractor has no control.

(d) A STD may follow its own procedures regarding the inclusion of warranty provisions in non-NHS Federal-aid contracts.

(e) In the case of a design-build project, the following requirements will apply instead of paragraphs (a) through (d) of this section.

(1) General project warranties may be used on NHS projects, provided:

(i) The term of the warranty is short (generally one to two years);

(ii) The warranty is not the sole means of acceptance;

(iii) The warranty must not include items of routine maintenance which are not eligible for Federal participation; and,

(iv) The warranty may include the quality of workmanship, materials and other specific tasks identified in the contract.

(2) Performance warranties for specific products on NHS projects may be used at the STD's discretion. If performance warranties are used, detailed performance criteria must be provided in the Request for Proposal document.

(3) The STD may follow its own procedures regarding the inclusion of war-

ranty provisions on non-NHS Federal-aid design-build contracts.

(4) For best value selections, the STD may allow proposers to submit alternate warranty proposals that improve upon the warranty terms in the RFP document. Such alternate warranty proposals must be in addition to the base proposal that responds to the RFP requirements.

[60 FR 44274, Aug. 25, 1995, as amended at 67 FR 75926, Dec. 10, 2002]

§ 635.417 Convict produced materials.

(a) Materials produced after July 1, 1991, by convict labor may only be incorporated in a Federal-aid highway construction project if such materials have been:

(1) Produced by convicts who are on parole, supervised release, or probation from a prison or

(2) Produced in a qualified prison facility and the cumulative annual production amount of such materials for use in Federal-aid highway construction does not exceed the amount of such materials produced in such facility for use in Federal-aid highway construction during the 12-month period ending July 1, 1987.

(b) *Qualified prison facility* means any prison facility in which convicts, during the 12-month period ending July 1, 1987, produced materials for use in Federal-aid highway construction projects.

[53 FR 1923, Jan. 25, 1988, as amended at 58 FR 38975, July 21, 1993]

APPENDIX A TO SUBPART D OF PART 635—SUMMARY OF ACCEPTABLE CRITERIA FOR SPECIFYING TYPES OF CULVERT PIPES

Type of drainage installation	Alternatives required			AASHTO designations to be included with alternatives	Application	Remarks
	Yes	No	Number			
Cross drains under high-type pavement. ¹	X	Statewide	Any AASHTO-approved material. ² Do. ²
Other cross-drain installations.	X	3 minimum	M-170 and M-190.do	
Side-drain installations	Xdo	M-36do	Do. ²
Special installation conditions.	X	Individual installation.	Specified to meet special conditions.
Special drainage systems (storm sewers, inverted siphons, etc.).	Xdo	Specified to meet site requirements.

¹ High-type pavement is generally described as FHWA construction type codes I, J, K, L, and plant mix and penetration macadam segments, respectively shown in the right-hand columns of type codes G and H having a combined thickness of surface and base of 7 in or more (or equivalent) or that are constructed on rigid bases.

²Types not included in currently approved AASHTO specifications may be specified if recommended by the State with adequate justification and approved by FHWA.

Subpart E—Interstate Maintenance Guidelines

SOURCE: 45 FR 20793, Mar. 31, 1980, unless otherwise noted.

§ 635.501 Purpose.

To prescribe Interstate maintenance guidelines and establish the policy and procedures to insure that the condition of Interstate routes is maintained at the level required by the purposes for which they were designed.

§ 635.503 Policy.

The policy of the FHWA is to insure that each State transportation department develops and implements an Interstate maintenance program conforming to the guidelines in this subpart. The maintenance program shall be consistent with practices deemed necessary to adequately provide for motorist safety, preservation of the highways, rideability, and aesthetics.

§ 635.505 Maintenance guidelines.

(a) The following critical elements should serve to direct the development and implementation of an Interstate maintenance program in each State.

(1) *Roadway surfaces.* Preservation of the structural integrity of the roadway and the safety and comfort of the user. This includes a safe, smooth, skid-resistant surface, as close as practical to the original, or subsequently improved, grade and cross section.

(2) *Shoulders.* Preservation of a safe, smooth surface which is free of obstruction, contiguous with the adjacent roadway surface, and as close as practical to the original, or subsequently improved, grade and cross section.

(3) *Roadside.* Preservation of the roadside in a safe, pleasant, and forgiving manner through vegetation management, erosion control, and litter pick-up.

(4) *Drainage.* Preservation of hydraulic capacity for which originally designed.

(5) *Bridges and tunnels.* Preservation of the structural and operational char-

acteristics for which originally designed. These include safe, smooth, skid-resistant surfaces; proper surface drainage; and adequate functioning bearing devices and substructural elements. Replacement or repair of structural railing and approach guardrail should be done without unreasonable delay. Tunnels should be cleaned, properly lighted, and adequately ventilated.

(6) *Snow and ice control.* Preservation of the roadway safety, efficiency, and environment during winter driving conditions.

(7) *Traffic control devices.* Preservation of clean, legible, visible, and properly functioning traffic control devices. This includes pavement markings, signing, delineators, signals, etc.

(8) *Safety appurtenances.* Replacement of damaged, defective, and/or inoperable devices without unreasonable delay. This includes guardrails, impact attenuators, breakaway supports, barriers, etc.

(9) *Safety rest areas.* Preservation and operation of facilities reasonably necessary for the convenience, relaxation, and informational needs of the user.

(10) *Access control.* Preservation of the originally designed access control, elimination of unauthorized traffic movement, and prevention of improper or unauthorized use of the highway rights-of-way.

(11) *Traffic safety in maintenance and utility work zones.* Procedures that will aid the safety of motorists and maintenance workers. The procedures shall be consistent with the provisions of 23 CFR part 630, subpart J, and part VI of the Manual on Uniform Traffic Control Devices.¹

(b) All replacements and repairs should conform to the currently approved design standards (23 CFR part 625) for all critical elements listed in

¹Available for purchase from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402 (GPO Stock Number 050-001-81001-8), and for inspection and copying as prescribed in 49 CFR 7, app. D.